Topological Methods in Nonlinear Analysis Volume 54, No. 1, 2019, 321–343 DOI: 10.12775/TMNA.2019.047

© 2019 Juliusz Schauder Centre for Nonlinear Studies

DECAY RATES FOR A VISCOELASTIC WAVE EQUATION WITH BALAKRISHNAN-TAYLOR AND FRICTIONAL DAMPINGS

BAOWEI FENG — YONG HAN KANG

ABSTRACT. In this paper we are concerned with a viscoelastic wave equation with Balakrishnan—Taylor damping and frictional damping. By using the multiplier method and some properties of convex functions, we establish general energy decay rates of the equation without imposing any growth assumption near the origin on the frictional term and strongly weakening the usual assumptions on the relaxation term. Our stability result generalizes the earlier related results.

1. Introduction

This paper is concerned with the following viscoelastic wave equation with Balakrishnan–Taylor and frictional dampings in $\Omega \times \mathbb{R}^+$,

(1.1)
$$u_{tt} - (\xi_1 + \xi_2 ||\nabla u||^2 + \sigma(\nabla u, \nabla u_t)) \Delta u + \int_0^t \operatorname{div}[a(x)g(t-s)\nabla u(s)] ds + \eta(t)b(x)h(u_t) = |u|^\rho u,$$

²⁰¹⁰ Mathematics Subject Classification. Primary: 35B40; Secondary: 74Dxx, 93D20. Key words and phrases. General decay; Balakrishnan–Taylor damping; weak frictional damping; convexity; memory.

The first author was supported by the National Natural Science Foundation of China Grant # 11701465.

The second author was supported by Basic Science Research Program through the National Research Foundation of Korea (NRF) funded by the Ministry of Education Grant # 2016R1A1B03930361.